查询LP379PBG1-C0G供应商

COTCO

P4 InGaN Green Ultra Bright LED

LP379PBG1−C0G





NOTES: 1. ALL DIMENSIONS ARE IN mm TOLERANCE IS.±0.25mm UNLESS OTHERWISE NOTED.
2. AN EPOXY MENISCUS MAY EXTEND ABOUT 1.5mm DOWN THE LEADS.
3. BURR AROUND BOTTOM OF EPOXY MAY BE 0.5 mm MAX.

Applications

Advertising signs
Indicators
Message board

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.	Unit
Forward Current	I_F	30	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	120.00	mW
Operating Temperature	T_{opr}	−20 ~ +75	°C
Storage Temperature	T_{stg}	−30 ~ +80	°C
Soldering Temperature	T_{sol}	260	°C
Soldering Time	−	for 3 sec. max	−

Opto−Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V_F	I_F=30mA	−	4.00	4.60	V
Reverse Current	I_R	V_R=5V	−	−	100	μA
Luminous Intensity	I_V	I_F=30mA	1000.00	2000.00	−	mcd
Viewing Angle	$2\theta^{1/2}$	−	−	120°	−	deg.
Peak Wavelength	λp	I_F=30mA	−	502	−	nm
Dominant Wavelength	λd	I_F=30mA	−	505	−	nm
Spectral Line Half Width	Δλ	I_F=30mA	−	38	−	nm

Company Headquarters
3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725

Marktech Optoelectronics
Web: www.marktechopto.com | Email: info@marktechopto.com

California Sales Office:
950 South Coast Drive, Suite 225
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314



FIG.1 FORWARD CURRENT VS. FORWARD VOLTAGE.



FIG.2 REVERSE CURRENT VS. REVERSE VOLTAGE.



FIG.3 RELATIVE LUMINOUS FLUX VS. FORWARD CURRENT.



FIG.4 RELATIVE LUMINOUS FLUX VS. WAVELENGTH.



FIG.5 MAXIMUM FORWARD DC CURRENT VS AMBIENT TEMPERATURE (Tjmax=95°C)



FIG.6 FAR FIELD PATTERN

1. Cathode PAD Area (0.18 X 0.18 X 2inch^2)
2. Height above nominal seating plane in inches(0.3inch)

Company Headquarters
3 Northway Lane North
Latham, New York 12110
Toll Free: 800.984.5337
Fax: 518.785.4725

Marktech Optoelectronics

Web: www.marktechopto.com | Email: info@marktechopto.com

California Sales Office:
950 South Coast Drive, Suite 225
Costa Mesa, California 92626
Toll Free: 800.984.5337
Fax: 714.850.9314